

Product Specification

AQUA AHF 215

Main Applications

- Drain and sewer cleaning
- Pipe and tube cleaning
- Pressure testing boilers, pipes & tanks
- High pressure water jet cleaning & descaling
- Water and water abrasive surface




- Relief and unloader valves
- Pneumatically actuated valves
- Foot valves
- Jetting guns
- Sandblasting attachments
- Jetting hose
- Drain/jetting nozzles and bombs
- Accumulators
 - Shaft diameter
 50mm (key 14 x 9 x 80)
 Inlet port
 2" BSP
 Discharge ports
 ½" 1 ¼" BSP
 Dimensions
 L1040 W565 H420
 Max fluid temperature
 60°C (140°F)
 Max inlet pressure
 4.57 bar (66psi)
 Pump Weight
 391kg

Flowplant Group Ltd

Gemini House, Brunel Road, Churchfields Industrial Estate, Salisbury, Wiltshire. SP2 7PU United Kingdom

t: +44 (0)1722 325 424 f: +44 (0)1722 411 329 e: sales@flowplant.co.uk

High Pressure Cleaner Solutions



Performance						
PLUNGER DIA mm	MOTOR POWER (kW)					
	110 kW		90 kW		75 kW	
	Max	Act	Max	Act	Max	Act
	Pressure	Flow	Pressure	Flow	Pressure	Flow
	Bar	L/min	Bar	L/min	Bar	L/min
21	1000	31.7	1000	31.7	1000	31.7
25	1000	46.6	1000	46.6	875	48.3
26	1000	50.7	1000	50.7	780	54.0
28	1000	60.0	800	63.5	650	66.4
32	785	81.0	600	85.2	475	88.0
35	640	99.4	490	103.5	395	106.1
38	525	120.0	410	123.7	330	126.2
40	465	135.2	365	138.8	295	141.2
45	360	174.6	285	178.0	230	180.4
48	315	200.8	245	204.4	200	206.7
50	285	219.3	225	222.7	185	224.9
53	250	248.8	200	252.0	160	254.4
55	230	270.0	185	273.0	150	275.4
57	215	291.8	170	295.1	140	297.2
60	190	326.8	150	329.6	125	331.6
65	160	387.1	125	390.4	100	392.7

All performances are nominal based on a pump crank shaft speed of 510 rpn
Flow indicated is maximum actual flow at zero pressure

Flowplants' policy is one of continuous improvement and the right is reserved to revise specifications without prior notice.



Flowplant Group Ltd provides the information herein in good faith but makes no representation as to its comprehensiveness or accuracy. This data sheet is intended only as a guide to Flowplant Group Ltd products and services. Individuals using this data sheet must exercise their independent judgment in evaluating product selection and determining product appropriateness for their particular purpose and system requirements. Flowplant Group Ltd MAKES NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, NICLIDING WITHOUT LIMITATION ANY WARRANTIES OF MERCHANTINESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE INFORMATION AFT PORDUCT(S) TO WHICH THE INFORMATION REFERS. ACCORDINGLY, Flowplant Group Ltd WILL ON'S BE RESPONSIBLE FOR DAMAGES (OF ANY KIND OR NATURE, INCLUDING INCIDENTAL, INDIRECT, OR CONSEQUENTIAL DAMAGES) RESULTING FROM THE USE OF OR RELIANCE UPON THIS INFORMATION. Flowplant Group Ltd reserves the right to change product designs and specifications without notice.