

200 Bar 対応
ターボ II チェーンカッター (リジット・セントライザー付)



200 bar

Turbo II Chain Cutter (Rigid centralizer)

TURBO II (Rigid Centralizer)

This innovative, highly reliable and efficient product offers superior drive and thrust. The chain retainer is driven by a high performance turbine thus achieving unsurpassed results in the removal of roots, grease and mineral deposits from 6" - 12" pipelines.

Advantages:

- Can be used in difficult pipe that has drop joints and offsets etc...
- Low maintenance (lubrication is not necessary)
- Easy and fast changeable chain retainers
- Capable of being used with recycled water
- Reduced water consumption
- Reduced operating costs

Applications:

For removing extensive root growth and total blockages. Also, for removing obstructions such as calcium, grease, scale and crust.

Technical Specs:

Capacity : min. 70 l/min, (15,7 gpm) at ca. 100 bar (1400 PSI)
Material : Aluminum / st. steel
WP : max. 200 bar (2.850 psi)
Connection : 1" BSPF - 3/4" BSPF - 1/2" BSPF
Medium : Recycling - drinking water
Dimensions : ø 150 mm with centralizer, length 230 mm.
Weight : 3 Kg

Part Number: 2250 Complete with chain / centralizer ø 150 mm. (6")
Part Number: 2251 Centralizer ø 150 mm.(6")
Part Number: 2252 Centralizer ø 200 mm (8")
Part Number: 2253 Centralizer ø 250 mm (10")
Part Number: 2254 Centralizer ø 300 mm (12")
Part Number: 2210 Chain included mounting ring ø 150 mm
Part Number: 2211 Chain included mounting ring ø 200 mm
Part Number: 2212 Chain included mounting ring ø 250 mm
Part Number: 2213 Chain included mounting ring ø 300 mm
Part Number: 2220 Chain / meter
Part Number: 2222 Chain st. st. / meter

このイノベティブで高い信頼性をもつ高効率プロダクトは、すぐれた回転と推進力を発揮します。チェーンリテイナーはハイパフォーマンス タービンによって回転させます。このことが6インチから12インチ程度のパイプラインでの根っ子の取り除きや、油汚れ・ミネラルの蓄積物の除去に最高の威力を発揮します。

- くぼみ・ジョイント・分岐があるような洗浄が困難なパイプの洗浄に使用することができます。
- 簡単なメンテナンス（潤滑油を必要としません）
- チェーンリテイナーを簡単・迅速に交換することができます
- リサイクルした水の使用にも耐えることができます。
- 水の消費量をおさえることができます。
- オペレーティングコストを抑えることができます。

スペック:

水量: 最小70L/分 (100Bar 設定時)

材質: アルミニウム/ステンレススチール

最高使用水圧: 200Bar

接続面: 1" BSPF - 3/4" BSPF - 1/2" BSPF

使用水質: リサイクル水-飲料水

寸法: ø 150mm (セントライザー込み)

長さ: ø 230mm

重量: 3kg

PRICE: ターボ II FIXED 1" @518,000

ターボ II FIXED 1"用セントライザー@51,800(150mm)@63,000(200mm)@75,600(250mm)@93,800(300mm)

有限会社ケイテック
URL: <http://k-tech-co-ltd.sakura.ne.jp>
E-MAIL: k-tech@m2.pbc.ne.jp
PHONE: 090-9846-7017