

250 Bar 対応
ターボ S400 チェーン カッター



このイノベティブで高い信頼性をもつ高効率プロダクトはすぐれた回転と推進力を発揮します。チェーンリテーナーはハイパフォーマンス タービンによって回転させます。このことが8インチから16インチ程度のパイプラインでの根っ子の取り除きや、油汚れ・ミネラルの蓄積物の除去に最高の威力を発揮します。

- 8インチから16インチの幅でスキッドを継続的に調整することができます。必要であれば0.25mm単位で調整することができます。
- それぞれの作業に応じてそれぞれのチェーンカッターアタッチメントと取りつけることによって、ターボS400のフレキシブル 多面的な能力を生かすことができます。
- くぼみ・ジョイント・分岐があるような洗浄が困難なパイプの洗浄に使用することができます。
- 簡単なメンテナンス（潤滑油を必要としません）
- チェーンリテーナーを簡単・迅速に交換することができます
- リサイクルした水の使用にも耐えることができます。
- 水の消費量をおさえることができます。
- オペレーティングコストを抑えることができます。

スペック：

水量：最小150L/分（100Bar 設定時）

材質：アルミニウム/ステンレス・スチール

最高使用水圧：250Bar

接続面：1"BSPP-3/4"BSPP

使用水質：リサイクル水-飲料水

寸法：Φ200mm-Φ400mm（セントライザー付）

長さ：Φ540mm

重量：12kg

250 bar

Turbo S400 Chain Cutter

TURBO S 400

This innovative, highly reliable and efficient product offers superior drive and thrust. The chain retainer is driven by a high performance turbine thus achieving unsurpassed results in the removal of roots, grease and mineral deposits from 8" - 16" pipelines.

Advantages:

- Continuously adjustable skid from 8"-16" and can be adjusted in 0,25 mm. (1/16") increments if necessary
- Different cutting attachments for different applications makes the Turbo S 400 Flexible versatile
- Can be used in difficult pipe that has drop joints and offsets etc...
- Low maintenance (lubrication is not necessary)
- Easy and fast changeable chain retainers
- Capable of being used with recycled water
- Reduced water consumption
- Reduced operating costs

Applications:

For removing extensive root growth and total blockages. Also, for removing obstructions such as calcium, grease, scale and crust.

Technical Specs:

Capacity : min. 150 l/min, (33,7 gpm) at ca. 100 bar (1400 PSI)

Material : Aluminum / st. steel

WP : max. 250 bar (3.570 psi)

Connection : 1"BSPP - ¾"BSPP

Medium : Recycling - drinking water

Dimensions : ø 200 mm - ø 400 mm. with centralizer, length 540 mm.

Weight : 12 Kg.

Part Number: 2500 Complete with chain / centralizer ø 200 mm. (8")

Part Number: 2510 Chain included mounting ring ø 200 mm

Part Number: 2511 Chain included mounting ring ø 250 mm

Part Number: 2512 Chain included mounting ring ø 300 mm

Part Number: 2513 Chain included mounting ring ø 350 mm

Part Number: 2514 Chain included mounting ring ø 400 mm

Part Number: 2515 Chain st. steel included mounting ring ø 200 mm

Part Number: 2516 Chain st. steel included mounting ring ø 250 mm

Part Number: 2517 Chain st. steel included mounting ring ø 300 mm

Part Number: 2518 Chain st. steel included mounting ring ø 350 mm

Part Number: 2519 Chain st. steel included mounting ring ø 350 mm

Part Number: 2520 Chain / meter

Part Number: 2522 Chain st. st. / meter

有限会社ケイテック

URL:<http://k-tech-co-ltd.sakura.ne.jp>

E-MAIL : k-tech@m2.pbc.ne.jp

PHONE : 090-9846-7017